

Semi-Auto Heat Transfer Machine

The HIX® S series semi-automatic clamshell heat presses are built off the time-tested HT models, the S series adds a mechanical auto open feature without the need for an air compressor that reduces operator fatigue by eliminating half of the manual effort. The auto open feature reduces the chance of scorched t-shirts and is helpful with longer transfer times such as sublimation designs on textile and non-textile substrates that take one to several minutes to complete.



S Series

Overview

- These presses feature a digital timer that is adjustable up to 99 minutes and 59 seconds, shows countdown on readout, beeps after elapsed time, and resets when the open and close handle is raised. With full range pressure adjustment to work with every project.
- The S Series now comes with a free Splitter Stand, allowing for the operators to "dress" the shirt easily over the lower platen, keeping the back of the shirt positioned underneath the machine and away from the heat and compression. This is handy when trying to avoid double-compression and heating of a previously applied transfer on the same shirt.
- Top Pressure Plate The handle attaches to a 4"x5" pressure plate on the top platen instead of a single screw going into the top platen. This provides more even pressure on the outside edges of the press. Think of it as pushing down with your entire hand versus just your thumb.
- The HIX® S Series Clamshell
 Presses utilizes an electronically
 activated mechanical latch
 release mechanism with a gas
 shock assist to help enhance
 and support your operations.
 This helps to reduce fatigue and
 increase productivity.
- Direct-To-Garment applications are also a large driving force in the success of the autoopen feature, allowing you the freedom of loading your printer while the last print is curing, eliminating any risk of scorching or compromising transfer quality due to overheating.
- No compressor required. Free operation, reduce fatigue, and increase productivity – all with one press.

FEATURES

- · All Metal Construction
- Integrated full color LCD touchscreen controller
- Up to four programmable presets
- Cantilevered Splitter Stand Included
- Large opening for easy shirt loading
- Lifetime warranty on heating element

S-450 Features

- 15" x 15" Heat Platen
- 120v or 220v

S-650 Features

- 16" x 20" Heat Platen
- 120v or 220v

TEMPERATURE RANGE

Off - 450°F (232°C) upper platen

CERTIFICATIONS

- · CE Certified
- ETL Certified to UL & CSA Standards

ACCESSORIES (Not Included)

- PTFE Sheet
- PTFE Pad Protector
- · Interchangeable Specialty Platen
- · Replacement Pad Kits







DIMENSIONS (W.H.D)

Width: 17 inches

Height: 31 inches (handle up)

Depth: 29 inches

Weight: Press only 80 lbs

SHIPPING DIMENSIONS

Shipping Width: 23 inches Shipping Height: 21 inches Shipping Depth: 34 inches Shipping Weight: 100 lbs

ELECTRICAL

120 Volt / 60 Hz 1500 Watts 12.5 Amps

220 Volt / 60 Hz 1650 Watts 7.5 Amps



DIMENSIONS (W,H,D)

Width: 17 inches

Height: 31 inches (handle up)

Depth: 29 inches

Weight: Press only 93 lbs

SHIPPING DIMENSIONS

Shipping Width: 23 inches Shipping Height: 21 inches Shipping Depth: 34 inches Shipping Weight: 105 lbs

ELECTRICAL

120 Volt / 60 Hz 1750 Watts 14.5 Amps

220 Volt / 60 Hz 2000 Watts 10 Amps

HIX® Corporation recommends all equipment is installed with surge protection & in a climate controlled environment for best results.



HIX® Corporation Graphics Division Product improvement may require specifications to change without notice hixcorp.com

800-835-0606

1201 E. 27th Terrace Pittsburg, KS 66762 USA





