

FACESTOCK DESCRIPTION: 70# Bright White Felt With 30% PCW Wet Strength, FSC® Certified

Bright white premium facestock with a felt finish that provides good print integrity and color reproduction. Featuring 30% post consumer waste content making it an excellent choice for eco-friendly applications. It is FSC® and Green Seal certified.



Basis Weight (25 x 38 / 500), lbs.	70
Caliper, mils	6.3
Brightness, %	88
Opacity, %	93
PCW, %	30
Recycled Content, %	30
Regulatory Compliances	FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, REACH, Green Seal Certified

ADHESIVE DESCRIPTION: i8017

i8017 is an ultra-aggressive permanent designed for difficult-to-label surfaces. It offers excellent initial tack and ultimate adhesion to a variety of substrates. i8017 is UV resistant, water resistant, and offers some solvent resistance.

Type	High Performance Acrylic
Classification	Acrylic
pH	Slightly Acidic
Minimum Application Temp., °F	20
Service Temperature Range, °F	-20 to +300
Regulatory Compliances	California Proposition 65, CONEG, Natural Rubber Latex Free, REACH, RoHS, FDA 21 CFR 175.105, FDA 21 CFR 175.125 (a) (b), FDA 21 CFR 176.180

LINER DESCRIPTION: 1.2 Mil Clear Polyester

A clear polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, mils	1.2
Yield, sq. in/lb	16,500
Tensile Strength, MD / TD, psi	29,900 / 29,900
Haze, %	3.5%
Elongation at break, MD / TD, %	100 / 100
Shrinkage at 302°F/30 min., MD / TD, %	2 / 0.4
Regulatory Compliances	CONEG, REACH

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

This product complies with Australian PFAS regulations effective 1 July 2025. For more information, please contact: sustainability@ballanddoggett.com.au