

70# Bright White Felt With 100% PCW, Wet Strength, FSC® Certified / H-318 / 1.2 Mil Clear 90% Recycled Polyester (r-PET)

FACESTOCK DESCRIPTION: 70# Bright White Felt With 100% PCW, Wet Strength, FSC® Certified

Bright white premium facestock with a felt finish that provides good print integrity and color reproduction. Featuring 100% post consumer waste content making it an excellent choice for eco-friendly applications. It is manufactured with "wet strength" properties to increase performance in moist environments. It is FSC® and Green Seal certified.



Basis Weight (25 x 38 / 500), gsm	103.3
Caliper, microns	157.5
Brightness, %	91
Tear, MD / CD, gF	65 / 75
Tensile, MD / CD, kg/15mm	9 / 7.5
PCW, %	100
Regulatory Compliances	FSC® Certified, FSC® is a voluntary program, and not legally required to be adhered to, Green Seal Certified

ADHESIVE DESCRIPTION: H-318

H-318 is the ideal choice for high end beverage and spirits, with improved resistance to moisture and humidity after bottling and at presentation to the consumer. H-318 is an aggressive, blended emulsion acrylic adhesive with the unique ability to combine special characteristics from different adhesives. H-318 was engineered to provide excellent high initial tack and quicker label adhesion onto glass while providing functional converting performance on an array of paper and film face stocks.

Type	Hybrid
Classification	Emulsion Acrylic
Minimum Application Temp., °C	-26
Service Temperature Range, °C	-29 to 79
Regulatory Compliances	FDA 21 CFR 175.105

LINER DESCRIPTION: 1.2 Mil Clear 90% Recycled Polyester (r-PET)

A clear 90% recycled content polyester film liner with high strength and durability. Typically used for high speed automatic roll-to-roll applications.

Caliper, Microns	30
Yield, N/mm2	115.611
Elongation at break, MD / TD, %	115 / 90
Haze, %	5
Tensile Strength, MD / TD, kg/cm2	1900 / 2000
Shrinkage at 302°F/30 min., MD / TD, %	3.0 / 1.0

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.

This product complies with Australian PFAS regulations effective 1 July 2025.
For more information, please contact: sustainability@ballanddoggett.com.au