

Product: Range: Digi Tuff Synthetic Specialty Door Hanger

Category: Small Format Digital - Synthetic

Technical specifications:

195HWT.3UPDH

3 Up Door Hanger Matt White Film

- Pre-perforated and print ready to personalise
- Matt white opaque suitable for full colour duplex printing
- Waterproof, tear-proof, greaseproof
- No need to laminate

Please Note: Keep all print a minimum of 4mm away from all perforations

Fold all perforations in both directions for easy removal of pieces from the sheet

Compatibility Guidance:

Suitable for most thermal transfer and dry toner (laser/LED/flash fusion) print processes, both mono and colour small-volume, mid-volume & production machines.

On such machines the user must establish for themselves the optimum settings and paper path, being aware of the thickness and weight of the material.

Recommended Conditions:

Printroom	10°C - 30°C	40% - 55% RH
Usage	-40°C - 120°C	10% - 100% RH
Storage	10°C - 20°C	20% - 55% RH

Available in A4

Also available in 145µ/5.7mil (145.3UPDH) and 195µ/7.7mil 6/page (195.6UPDH)

Thickness (195µ/7.7mil) Weight (260gsm)

Digital Compatibility

- Colour Laser Printers & Copiers
- Dry toner

Applications Include

- Price labels
- Direct mail applications
- Warning stickers
- POS applications
- Marketing signage