

EZ Floor Outdoor

EZ Floor Outdoor is a PVC-free Multi-Core Aluminium/ PP floor graphic construction system which increases strength, reduce the risk of stretching or film splitting. This print-ready PVC-free film with high conformability and optimised pressure sensitive adhesive ideal for exterior floor signage application.

- ✓ Advanced sharkskin-effect coating. Recommend UV inkjet for highest durability
- ✓ No lamination required
- ✓ A more aggressive texture surface and R12 outdoor anti-slip certification, suitable for Low slip potential in dry & wet conditions
- ✓ 3-6 months exterior durability (dependant on traffic and surface)
- ✓ Roll available in 1220mm x 25M
- ✓ Perfect and conformable for outdoor applications on concrete paving, bitumen, brickwork and asphalt or uneven surfaces for up to 3 to 6 month's exterior durability
- ✓ Printable on (eco) solvent, latex and UV Inkjet printing technology

Property	Typical Value	Unit	Test Method
Construction			
Total Thickness	373 +/- 10	μ	Electronic Micrometer
Total Weight	335 +/- 8	gsm	Internal method
Face Material (without PSA)			
Thickness	200 +/- 6	μ	Electronic Micrometer
Weight	147 +/- 5	gsm	Internal method
Adhesive			
Thickness	55 +/- 5	μ	Electronic Micrometer
180° Peel Adhesion (SS)	32 +/- 3	N/25mm	
Adhesive Application Temperature	+5 to +50	°C	Internal method
Adhesive Service Temperature	-40 to +120	°C	Internal method
Liner			
Liner Thickness	118 +/- 5	μ	Electronic Micrometer
Liner Weight	130 +/- 5	gsm	Internal method

Recommended Conditions

Print Room	10°C - 30°C	30% - 65% RH
Usage	-40°C - 120°C	10% - 90% RH
Storage	10°C - 20°C	20% - 20% RH

f t @ in p

1300 024 749

ballanddoggett.com.au

Ball & Doggett