

Technical specification sheet

Ball & Doggett
ballanddoggett.com.au

Product: Yupo Octopus Eco Solvent WKE250

Category: Display & Visual - Solvent, Latex, Eco Solvent

Country of Origin: Japan



Technical specifications:

Parameter	Unit	Range
Thickness, Thickness, Average	micron	275 ± 32
Basis Weight, Average	g/m2	200.0 ± 25.0
Gloss, Average - Printsides	%	40 ± 7
Whitenss, Average	WI	92min
Material face stock	Polypropylene	
Suction layer Back	Acyrlc resin	
Liner	Polyethylene, clear	

Conversion+

- | | |
|---|---|
| ☐ Flat bed cutters | ☐ Cold overlaminating |
| ☐ Friction fed cutters | ☐ Electrostatic printing |
| ☐ Die cutting | ☒ Latex inkjet (trialling recommended) |
| ☐ Thermal transfer | ☒ Eco Solvent inkjet |
| ☐ Screen printing | ☐ Solvent inkjet |
| ☐ Offset printing | ☒ UV curable inkjet |

+Always test with your combination of printer and inks prior to commercial use.

Roll Sizes

1270mm x 20m 123785

Common Applications

Posters

Indoor POS Signage

Window Graphics

Bumper bar stickers

Signage