

Technical specification sheet

Ball & Doggett

ballanddoggett.com.au

Product: Plasnet PP SX

Category: Tickets & Tags: Synthetic

Origin: Taiwan

Technical specifications:

Description:	PLASNET SX is a White Calendered Polyolefin Sheet, uniquely manufactured to exhibit an extremely high tensile strength for applications requiring resistance to tearing and/or stretching. Its unique surface treatment also enables printing via screen, offset, gravure, flexography, letterpress and thermal transfer. (Printing recommendations available upon request)
Application:	/ Horticultural Tags, Baggage Tags, Maps, Long Life Tags, Bunting & Flags
Characteristics:	/ Superior Strength / Matte or Gloss Finish / Available Excellent printability and adhesion / Outstanding anti-static properties / Easy cutting, perforating and folding / Excellent UV stability Excellent cold crack resistance
Food Contact:	Conforms to USA legislation – FDA 21 CFR 177-1520
Treatment:	Both sides
Std Thickness:	0.10 mm(108gsm) – 0.25mm(270gsm)
Roll Availability:	330mm – 1830mm
Sheet Availability:	Minimum 450mm(SG) x 450mm(LG) Maximum 1600mm(SG) x 1200mm(LG)

ITEM		UNIT	RESULT	METHOD
			216gsm Matte	
Gauge		%	± 5	MICROMETER
Tensile Strength	MD	%	5098	ASTM – D638
	CD		3502	
Elongation	MD	%	1069	ASTM – D638
	CD		892	
Surface Tension	Outside	Gm/mm	46	ASTM – D2578
	Inside		46	
Roughness	Outside	-	17-24	JIS –B0601
	Inside		53-59	
Gloss level (60°)	Outside	-	3.5	ASTM – D523
	Inside		3.7	
Transmittance		%	11.4	ASTM – D1003
Whiteness		W	91.5	ASTM – E313
Surface			8 ^ 10/10	ASTM – D257
Resistance		Ω	0.20mm	MICROMETER
Test thickness		M2 / kg	4.54	-
Yield		-	1.08	ASTM – D792
Density				

This product complies with Australian PFAS regulations effective 1 July 2025.
For more information, please contact: sustainability@ballanddoggett.com.au

