

Technical specification sheet

Ball & Doggett
ballanddoggett.com.au

Product: Jellyfish Solvent PET Optically Clear



Category: Display & Visual - Solvent, UV Ink jet

Country of Origin: Korea

Technical specifications:

Parameters	Unit	Range
Caliper	micron	175
PET	microns	75
Coating	microns	25
Glue	microns	25
Weight	g/m2	225
Surface	ULTRA transparent (clear)	

Guidelines

- Printing Tip** Suitable printing condition: Temperature 15~30°C (59~86°F) / Humidity 30~60%
It is recommended to set up pre and post heaters around 30°C (86°F).
It is necessary to dry up and not to overlap the printed material before drying up.
- Lamination:** Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, overlamine is recommended.
- Storage:** It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F). Relative Humidity 50% RH
- Shelf Life:** One year stored in original package in recommended condition.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

Conversion⁺

- | | | |
|--|--|---|
| ☐ Flat bed cutters | ☐ Cold overlaminating | ☐ Latex |
| ☐ Friction bed cutters | ☐ Aqueous (dye & pigment) | ☒ Solvent |
| ☐ Die cutters | ☐ Screen printing | ☒ Eco Solvent |
| ☐ Thermal transfer screen | ☐ Printing offset | ☒ UV Ink jet |

⁺Always test with your combination of printer and inks prior to commercial use

Roll Sizes

1370mm x 30m	123322
1370mm x 50m	142261
1370mm x 200m	149097

Common Applications

Stickers and indoor POS signage

Road Shop (window advert) - Fashion, Sports, Electronics, Vehicle, Deli, Coffee etc

Indoor (window advert) - retail promotions, TV and White good applications

Updated: 06.22

